

100 JC20 Rec'd PCT/PTO 28 MAR 2002

"Express Mail" mailing label No

Date of Deposit

EL 90183364505
March 28, 2002

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the BOX PATENT APPLICATION, Assistant Commissioner for Patents, Washington, D C 20231

RON CADA

(Typed or printed name of person mailing paper or fee)

(Signature of person mailing paper or fee)

FORM-PTO-1390
(Rev. 9-2001)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

**TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371**

025265-232

U.S. APPLICATION NO. (If known, see 37 CFR 1.5)

10/089781

INTERNATIONAL APPLICATION NO.
PCT/AU00/01196

INTERNATIONAL FILING DATE
29 September 2000 (29.09.2000)

PRIORITY DATE CLAIMED
1 October 1999 (01.10.1999) and
5 October 1999 (05.10.1999)

TITLE OF INVENTION
PROGRESSIVE LENS

APPLICANT(S) FOR DO/EO/US

Michael Alan Morris, Scott Warren Fisher, Saulius Raymond Varnas and David Robert Pope

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (21) indicated below.
4. ☒ The US has been elected by the expiration of 19 months from the priority date (Article 31).
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is attached hereto (required only if not communicated by the International Bureau).
 - b. ☒ has been communicated by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ An English language translation of the International Application as filed (35 U.S.C. 371(c)(2))
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
 - b. ☒ have been communicated by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☐ have not been made and will not be made.
8. ☒ An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An unexecuted oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).

Items 11 to 20 below concern document(s) or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.
14. ☐ A second copy of the published international application under 35 U.S.C. 154(d)(4).
15. ☐ A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).
16. ☒ Other items or information:

A copy of International Publication No. WO 01/25837 published on 12 April 2001 (12.04.2001); Information Disclosure Statement Transmittal Letter; and Form 1449



21839

1010 RESUB OFFICE 28 MAR 2002

APPLICATION NO. (if known see 37 CFR 1.51) **107089731** INTERNATIONAL APPLICATION NO **PCT/AU00/01196** ATTORNEY'S DOCKET NUMBER **025265-232**

17: <input checked="" type="checkbox"/> The following fees are submitted				CALCULATIONS		PTO USE ONLY	
Basic National Fee (37 CFR 1.492(a)(1)-(5)): Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO \$1,040.00 (960) International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO \$890.00 (970) International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$740.00 (958) International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$710.00 (956) International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) \$100.00 (962)							
ENTER APPROPRIATE BASIC FEE AMOUNT =				\$	1,040.00		
Surcharge of \$130.00 (154) for furnishing the oath or declaration later than months from the earliest claimed priority date (37 CFR 1.492(e)). 20 <input type="checkbox"/> 30 <input type="checkbox"/>				\$			
Claims	Number Filed	Number Extra	Rate				
Total Claims	34 - 20 =	14	X \$18.00 (966)	\$	252.00		
Independent Claims	3 - 3 =	0	X \$84.00 (964)	\$	0		
Multiple dependent claim(s) (if applicable)			+ \$280.00 (968)	\$	0		
TOTAL OF ABOVE CALCULATIONS =				\$	1,292.00		
Reduction for 1/2 for filing by small entity, if applicable (see below). +				\$	0		
SUBTOTAL =				\$	1,292.00		
Processing fee of \$130.00 (156) for furnishing the English translation later than months from the earliest claimed priority date (37 CFR 1.492(h)). 20 <input type="checkbox"/> 30 <input type="checkbox"/>				\$	0		
TOTAL NATIONAL FEE =				\$	1,292.00		
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 (581) per property +				\$	0		
TOTAL FEES ENCLOSED =				\$	1,292.00		
				Amount to be refunded:	\$		
				charged:	\$		

- a. ☐ Small entity status is hereby claimed.
- b. ☒ A check in the amount of \$ 1,292.00 to cover the above fees is enclosed.
- c. ☐ Please charge my Deposit Account No. 02-4800 in the amount of \$ to cover the above fees. A duplicate copy of this sheet is enclosed.
- d. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 02-4800. A duplicate copy of this sheet is enclosed

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

James W. Peterson
BURNS, DOANE, SWECKER & MATHIS, L.L.P.
P.O. Box 1404
Alexandria, Virginia 22313-1404
(650) 622-2300

SIGNATURE

James W. Peterson

NAME

26,057

REGISTRATION NUMBER

March 28, 2002

DATE

PROGRESSIVE LENS

The present invention relates to a progressive ophthalmic lens and in particular to a progressive ophthalmic lens exhibiting improved functionality and ease of adaptation, particularly for the first-time or part-time wearer, and taking
5 into account wearer sensitivity to swim, and to a process for producing such lenses.

Numerous progressive lenses are known in the prior art. Progressive lenses have heretofore been designed on the basis that they have distance, near and intermediate viewing zones. The intermediate zone joins the near and
10 distance zones in a cosmetically acceptable way, in the sense that no discontinuities in the lens should be visible to people observing the lens of the wearer. The design of the intermediate zone is based on a line called the "eye path" along which the optical power of the lens increases more or less uniformly.

However, prior art progressive lenses present the wearer with significant
15 adaptation difficulties. For example, a wearer who utilises progressive lenses for reading purposes may generally be inconvenienced by the limited width of vision for near tasks. Similarly, new progressive spectacle wearers may be sensitive to swim and may be unable or unwilling to learn new head postures dictated by prior art progressive lenses.

20 It would be a significant advance in the art if the progressive lens could more closely relate to the requirements of the individual wearer and to the natural eye movements of a wearer in performing intermediate and near tasks in particular and thus make adaptation to a progressive prescription easier.

Accordingly, it is an object of the present invention to overcome, or at least
25 alleviate, one or more of the difficulties and deficiencies related to the prior art. These and other objects and features of the present invention will be clear from the following disclosure.

Accordingly, in a first aspect of the present invention, there is provided a

progressive ophthalmic lens element including a lens surface having

an upper viewing zone having a surface power corresponding to distance vision,

5 a lower viewing zone having a greater surface power than the upper viewing zone to achieve a refracting power corresponding to near vision; and

an intermediate zone extending across the lens element having a surface power varying from that of the upper viewing zone to that of the lower viewing zone and including a corridor of relatively low surface astigmatism;

10 the lens surface including
a relatively high, relatively wide lower viewing zone; and
a relatively wide intermediate zone.

The present invention accordingly provides a progressive ophthalmic lens element exhibiting a balance in zone sizes which provides the wearer with significantly improved near and intermediate vision, thus making spectacles
15 including the progressive ophthalmic lenses more acceptable to the first time or part-time wearer, or a wearer with a near vision priority, and making adaptation thereto a much simpler task.

We may estimate the size of the zone on the lens surface available for clear vision by ray tracing the lens in the as worn configuration for a specific object
20 distance and calculating the area within an Add/4 diopter contour of the RMS power error inside a circle of the 22 m radius centred on the geometric centre (GC).

Preferably, the area of the lower viewing zone when ray traced to a 0.4 m object distance is over 150 mm².

25 In a further preferred aspect, the progressive lens design according to this aspect of the present invention may be such that the ratio of the area of clear vision of the upper (or distance) viewing zone to the lower (or near) viewing zone is in the range between approximately 2.50 and 3.00.

This clear vision size ratio is indicative of effective relative zone sizes and

In a still further preferred aspect of the present invention, the progressive lens design may exhibit a small amount of addition power (eg. 0.05 D to 0.4 D), proximate the fitting cross depending on the nominal addition power of the lens element and the base curve.

5 Applicants have found that the introduction of a small amount of addition power at the fitting cross aids the wearer in adapting to the progressive ophthalmic lens, particularly in respect of intermediate vision. The corridor of the intermediate viewing zone is thus effectively extended a small distance into the upper (or distance) viewing zone, allowing peripheral blur values to be reduced and the
10 zone available for clear vision at intermediate distances to be increased.

It will be understood that the ophthalmic lens element according to the present invention may form one of a series of lens elements.

Accordingly, in a further aspect of the present invention, there is provided a series of progressive ophthalmic lens elements, each lens element including a
15 lens surface having

an upper viewing zone having a surface power to achieve a refracting power corresponding to distance vision;

a lower viewing zone having a greater surface power than the upper viewing zone to achieve a refracting power corresponding to near vision; and

20 an intermediate zone extending across the lens element having a surface power varying from that of the upper viewing zone to that of the lower viewing zone and including a corridor of relatively low surface astigmatism;

the progressive ophthalmic lens series including

lens elements having a base curve suitable for use in providing a range of
25 distance prescriptions for one or more of emmetropes, hyperopes and myopes, each lens element differing in prescribed addition power and including a progressive design including

a relatively high, relatively wide lower viewing zone and

a relatively wide intermediate zone; the dimensions of the intermediate and
30 lower viewing zones being related to the prescribed addition power of the wearer.

The present invention accordingly relates to a progressive ophthalmic lens series exhibiting improved functionality and ease of adaptation, as it takes into account factors including one or more of the following: wearers' sensitivity to swim and natural eye movements. The progressive lens element within the series also

5 exhibits a distance/near zone balance more appropriate for a part-time wearer or a wearer with a near vision priority than those provided by general purpose prior art progressive lenses.

As stated above, each progressive ophthalmic lens element in a series according to the present invention exhibits a relatively high lower viewing, or near

10 vision, zone. The relatively high lower viewing zone may reduce the need for the wearer to learn new head postures for reading purposes.

Preferably the lens elements having a base curve suitable for emmetropes have an upper viewing zone and lower viewing zone such that the ratio of the area of clear vision of the upper viewing zone to the lower viewing zone is in the range

15 between approximately 2.50 and 3.00.

In a preferred embodiment of this aspect of the present invention, each lens element in the series may have a progressive lens design exhibiting a small amount of addition power proximate the fitting cross; the addition power component proximate the fitting cross being related to the prescribed addition

20 power and/or depth of focus of the wearer.

Preferably, the addition power proximate the fitting cross of a progressive lens element is in the range from 0.05 to 0.40 D, the fitting cross addition power increasing with the addition power for each of the base curves, and with the increasing base curve for each addition power.

25 The lens elements may exhibit an increase in corridor length within increasing addition power.

For example, for low to medium addition powers from approximately 1.0 D to 2.50 D, the relatively high, relatively wide lower viewing zone may permit useful

reading from a point (the highest reading point) approximately 10 to 12 mm below the fitting cross. Thus the effective corridor length is approximately 10 to 12 mm.

For higher addition powers, eg. from approximately 2.50 D and above, the lower viewing zone may permit useful reading from a point (the highest reading point) approximately 12 mm below the fitting cross. Then the effective corridor length is approximately 12 mm. It will be understood that the slight increase in effective corridor length at higher addition powers permits an increased effective lower or near viewing zone size and/or lower peripheral blur.

By the term "highest reading point" we mean the highest point along the eye path where the wearer can read normal size text at the 40 cm reading distance without perceiving the blur. This is equal to the nominal prescribed add minus the effective depth of focus for near vision which is around 0.50 D for a broad range of addition powers.

In a further preferred embodiment of this aspect of the present invention, the progressive lens design of each lens element in this series includes a surface correction to reduce or minimise the phenomenon of "swim".

The surface modification to reduce swim may be provided within a pair of generally horizontally disposed opposed segments generally centred at the fitting cross of each ophthalmic lens element. The opposed segments may extend approximately $\pm 22.5^\circ$ above and below a generally horizontal axis passing through the fitting cross.

The opposed segments may have a radius of approximately 15 mm from the fitting cross, preferably approximately 20 mm, more preferably approximately 25 mm.

The swim surface correction(s) may be such as to reduce optical aberrations contributing to swim. The swim surface correction(s) may take the form of a reduction in the sagittal addition power variations within the segments defined above.

Preferably, the difference between maximum and minimum sagittal addition power within the opposed segments is less than approximately $0.75 \times \text{Add}$ (in diopters)

5 In a preferred embodiment of this aspect of the present invention, the progressive design of each lens element within the series exhibits a substantially constant ratio of the area of clear vision of the upper (or distance) viewing zone to the lower (or near) viewing zone for all addition powers. The clear vision zone size ratio may generally be in the range between approximately 2.50 and 3.00.

10 The generally constant clear vision zone size ratio may thus provide the wearer with a generally constant area for clear foveal vision independent of addition power.

15 In a further preferred embodiment of this aspect of the present invention, the progressive lens design of each lens element within the series exhibits a substantially constant area of clear vision on the lens surface within the lower viewing zone for a specified base curve. Accordingly the design of each progressive lens element within the series provides the wearer with a generally constant, improved area of clear vision for near tasks across a range of addition powers.

20 Preferably, the lens element series according to Claim 21, wherein the lens element series exhibits a slight decrease in the area of the zone clear for distance vision on the lens surface inside a 22 mm radius circle centred on the GC and constrained by the $\text{Add}/4$ diopters RMS power error contour ray traced in the as worn configuration for an infinite object distance with increasing base curve.

25 By the term "corridor", we mean an area of the intermediate zone of varying power bounded by nasal and temporal contours of tolerable aberration for foveal vision.

The corridor has a "corridor length" (L), which corresponds to the length of the segment of the visual fixation locus which extends from the vertical height of

preferably vary from approximately 0.40 to 0.60.

In a preferred aspect of the present invention, the location of the corridor of the ophthalmic lens element may be dictated at least in part by the visual fixation locus;

- 5 the visual fixation locus being inset generally horizontally nasally below the fitting cross (FC) of the lens element.

By the term "visual fixation locus", as used herein, we mean the set of points which are the intersection of the lens surface and the patient's line of sight as he or she fixates on objects in the median plane. The term does not signify a
10 required, continuous eye movement path. Rather, the visual fixation locus indicates the set of points corresponding to variously positioned objects in the median plane.

As will be explained in detail below, the visual fixation locus takes into account the fact that the wearer may or may not use the accommodative reserve
15 for a particular fixation. As a result, points at different locations in the visual fixation locus are provided having a power sufficient for comfortable use at the appropriate object distances.

The fitting cross (FC) is generally located at $(0, y_{FC})$. The value of y_{FC} may vary, for example, from approximately 2 mm to 6 mm above the geometric centre
20 of the lens element.

Mathematical Description of Lens Surface

In a still further aspect of the present invention, there is provided a method of designing an ophthalmic lens element including a first lens surface having
an upper viewing zone having a surface power corresponding to distance
25 vision,

a lower viewing zone having a greater surface power than the upper viewing zone to achieve a refracting power corresponding to near vision; and
an intermediate zone extending across the lens element having a surface

power varying from that of the upper viewing zone to that of the lower viewing zone and including

a corridor of relatively low surface astigmatism; the ophthalmic lens element including

5 a relatively high, relatively wide lower viewing zone; and

a relatively wide intermediate zone,

which method includes

selecting a merit function relating to at least one optical characteristic of the lens to be minimised with an appropriate distribution of the optimisation

10 weights on the lens surface; and

solving the global minimisation problem using the Finite Element Method;

and

fabricating an ophthalmic lens element having a lens surface shaped according to said optimised surface description.

15 The ophthalmic lens element may be formulated from any suitable material. A polymeric material may be used. The polymeric material may be of any suitable type. The polymeric material may include a thermoplastic or thermoset material. A material of the diallyl glycol carbonate type, for example CR-39 (PPG Industries) may be used.

20 The polymeric article may be formed from cross-linkable polymeric casting compositions, for example as described in Applicants' United States Patent 4,912,155, United States Patent Application No. 07/781,392, Australian Patent Applications 50581/93, 50582/93, 81216/87, 74160/91 and European Patent Specification 453159A2, the entire disclosures of which are incorporated herein by
25 reference.

The polymeric material may include a dye, preferably a photochromic dye, which may, for example, be added to the monomer formulation used to produce the polymeric material.

The ophthalmic lens element according to the present invention may further
30 include standard additional coatings to the front or back surface, including

electrochromic coatings.

The front lens surface may include an anti-reflective (AR) coating, for example of the type described in United States Patent 5,704,692 to Applicants, the entire disclosure of which is incorporated herein by reference.

- 5 The front lens surface may include an abrasion resistant coating. e.g. of the type described in United States Patent 4,954,591 to Applicants, the entire disclosure of which is incorporated herein by reference.

10 The front and back surfaces may further include one or more additions conventionally used in casting compositions such as inhibitors, dyes including thermochromic and photochromic dyes, e.g. as described above, polarising agents, UV stabilisers and materials capable of modifying refractive index.

15 The present invention will now be more fully described with reference to the accompanying figures and examples. It should be understood, however, that the description following is illustrative only and should not be taken in any way as a restriction on the generality of the invention described above.

In the figures:

20 Figure 1 illustrates contour plots of Surface Astigmatism of a series of optical lens elements according to the present invention, with a base curve of 5.00 D (intended for emmetropes) and having addition powers in the range of 1.00 D to 2.75 D.

Figure 2 illustrates contour plots of Surface Mean Power for the optical lens elements according to Figure 1.

25 Figure 3 illustrates contour plots of optical RMS Power Error of the optical lens elements according to Figures 1 and 2. Ray tracing has been carried out with the model lens in the material with refractive index of 1.537 having the front surface as shown in Figures 1 and 2 with the base curve of 5.00 D, a spherical

back surface of 4.95 D, zero prism at the prism reference point and centre thickness of 2 mm; located in the front of the eye at a 27 mm back vertex distance from the centre of rotation of the eye and tilted pantoscopically by 7 degs. The assumed object field of the ray trace has a vertically varying distance starting at
5 infinity (the dioptric distance of 0.00 D) for all rays crossing the front lens surface at elevations above the FC, through a linearly decreasing object distance below the FC up to the NMP, where the object distance was 0.4 m (2.5 D) for all adds up to 2.50 D, and staying constant along each ray at 0.4 m for elevations below the NMP. In the case of the 2.75 D add the near object distance was slightly shorter –
10 0.36 m (2.75 D). In calculating the mean power error of the ray traced image as perceived by the wearer it has been assumed that the wearer has up to (2.5 - Add) D of reserve accommodation enabling him/her to cancel the negative mean power errors up to that magnitude in the lower part of the lens.

Figures 4 a and b illustrate RMS power error contour plots ray traced for
15 distance objects (object distance of infinity) and near objects (object distance of 0.40 m), respectively for a selection of optical lens elements from the series illustrated in Figure 3. (Addition Powers 1.50 D, 2.00 D and 2.50 D). The wearer's distance prescription was assumed to be plano sphere. The areas of clear vision are defined by a limiting contour of RMS power error equivalent to Add/4 (in
20 Diopters) inside a circle of 22 mm radius centred on a point 4 mm below the fitting cross, which will often coincide with the geometric centre of the lens. Zones are coloured pale grey, their size is indicated in mm².

Figure 5 illustrates contour plots of Surface Astigmatism of a series of optical lens elements according to the present invention, with a base curve of
25 2.75 D (intended for myopes) and having addition powers in the range of 1.00 D to 2.75 D.

Figure 6 illustrates contour plots of Surface Mean Power for the optical lens elements according to Figure 5.

Figure 7 illustrates contour plots of optical RMS Power Error for the optical
30 lens elements according to Figures 5 and 6. Ray tracing has been carried out with

Figure 10 illustrates contour plots of Surface Mean Power for the optical
30 lens elements according to Figure 9.

Figure 11 illustrates contour plots of optical RMS Power Error for the optical lens elements according to Figures 9 and 10. Ray tracing has been carried out with the model lens in the material with refractive index of 1.537 having the front surface as shown in Figures 9 and 10 with the base curve of 6.50 D, a spherical
 5 back surface of 3.65 D, zero prism at the prism reference point and centre thickness of 4 mm; located in the front of the eye at a 27 mm back vertex distance from the centre of rotation of the eye and tilted pantoscopically by 7 degs. The assumed object field of the ray trace has a vertically varying distance starting at infinity (the dioptric distance of 0.00 D) for all rays crossing the front lens surface
 10 at elevations above the FC, through a linearly decreasing object distance below the FC up to the NMP, where the object distance was 0.4 m (2.5 D) for all adds up to 2.50 D, and staying constant along each ray at 0.4 m for elevations below the NMP. In the case of the 2.75 D add the near object distance was slightly shorter – 0.36 m (2.75 D). In calculating the mean power error of the ray traced image as
 15 perceived by the wearer it has been assumed that the wearer has up to (2.5 - Add) D of reserve accommodation enabling him/her to cancel the negative mean power errors up to that magnitude in the lower part of the lens.

Figures 12 a and b illustrate RMS power error contour plots ray traced for distance objects (object distance of infinity) and near objects (object distance of
 20 0.40 m), respectively for a selection of optical lens elements from the series illustrated in Figure 11. (Addition Powers 1.50 D, 2.00 D and 2.50 D). The wearer's distance prescription was assumed to be +3.00 D sphere. The areas of clear vision are defined by a limiting contour of RMS power error equivalent to Add/4 (in diopters) inside a circle of 22 mm radius centred on a point 4 mm below
 25 the fitting cross, which will often coincide with the geometric centre of the lens. Zones are coloured pale grey, their size is indicated in mm².

It will be understood that the invention disclosed and defined in this specification extends to all alternative combinations of two or more of the individual features mentioned or evident from the text or drawings. All of these
 30 different combinations constitute various alternative aspects of the invention.

It will also be understood that the term "comprises" (or its grammatical

variants) as used in this specification is equivalent to the term “includes” and should not be taken as excluding the presence of other elements or features.

CLAIMS

1. A progressive ophthalmic lens element including a lens surface having

an upper viewing zone having a surface power corresponding to distance
5 vision,

a lower viewing zone having a greater surface power than the upper viewing zone to achieve a refracting power corresponding to near vision; and

an intermediate zone extending across the lens element having a surface power varying from that of the upper viewing zone to that of the lower viewing
10 zone and including a corridor of relatively low surface astigmatism;

the lens surface including

a relatively high, relatively wide lower viewing zone; and

a relatively wide intermediate zone wherein the upper viewing zone and lower viewing zone are such that the ratio of the area of clear vision of the upper
15 viewing zone to the lower viewing zone is less than approximately 3.00 and greater than approximately 2.50.

2. A progressive ophthalmic lens according to claim 1 wherein the area of the lower viewing zone inside a 22 mm radius circle centred on the geometric centre and constrained by the Add/4 diopters RMS power error contour for a 0.4 m
20 reading distance, is greater than approximately 150 mm^2 , and

the height of the lower viewing zone defined by the Add/4 diopters RMS power error contour is in the range of approximately 10 to 12 mm below the fitting cross.

3. A progressive ophthalmic lens element according to Claim 1, further
25 including a surface correction(s) in the peripheral regions of the lens element which functions to reduce or minimise optical aberrations contributing to the phenomenon of swim.

4. A progressive ophthalmic lens element according to Claim 3, wherein the surface correction(s) function to reduce optical aberrations in lens surface
30 areas including a pair of generally horizontally disposed opposed sectors

ART 34 AMDT

approximately $\pm 22.5^\circ$ above and below a generally horizontal axis passing through the fitting cross of the lens element.

5. A progressive ophthalmic lens element according to Claim 4, wherein the opposed sectors have a radius of approximately 15 mm from the fitting cross.

5 6. A progressive ophthalmic lens element according to Claim 4, wherein the opposed sectors have a radius of approximately 20 mm from the fitting cross.

7. A progressive ophthalmic lens element according to Claim 3, wherein the surface correction(s) provides a reduction in variation of the sagittal addition power within the opposed sectors.

10 8. A progressive ophthalmic lens element according to Claim 7, wherein the surface correction(s) is such that the difference between maximum and minimum sagittal addition power is less than approximately 0.75* Add diopters.

9. A progressive ophthalmic lens element according to Claim 1, wherein the lens design exhibits a small amount of addition power proximate the fitting cross, depending on the nominal addition power of the lens element.

15 10. A progressive ophthalmic lens element according to Claim 9, wherein the lens design exhibits approximately 0.05 D to 0.4 D of addition power proximate the fitting cross, depending on the nominal addition power of the lens element.

11. A progressive ophthalmic lens element according to Claim 1, further including a surface correction to improve optical properties proximate the peripheries of the lens element.

12. A progressive ophthalmic lens element according to Claim 11, wherein the distribution of RMS power error is varied proximate the peripheries of the upper and/or lower viewing zones to improve peripheral vision.

25 13. A progressive ophthalmic lens element series according to Claim 12, wherein the distribution of RMS power error exhibits a relatively low gradient

proximate the distance periphery and a relatively high gradient proximate the near periphery.

14. A progressive ophthalmic lens element according to Claim 13, wherein the ratio of the maximum rate of change of the ray traced RMS power error along the 12 mm long vertical lines centred on the fitting cross (FC) and horizontally offset 15 mm from the FC to the maximum horizontal rate of change of the RMS power error at the level of the near vision measurement point (NMP) varies from approximately 0.4 to approximately 0.6.

15. A series of progressive ophthalmic lens elements, each lens element including a lens surface having

an upper viewing zone having a surface power to achieve a refracting power corresponding to distance vision;

a lower viewing zone having a greater surface power than the upper viewing zone to achieve a refracting power corresponding to near vision; and

15 an intermediate zone extending across the lens element having a surface power varying from that of the upper viewing zone to that of the lower viewing zone and including a corridor of relatively low surface astigmatism;

the progressive ophthalmic lens series including

20 lens elements having a base curve suitable for use in providing a range of distance prescriptions for one or more of emmetropes, hyperopes and myopes, each lens element differing in prescribed addition power and including a progressive design including

a relatively high, relatively wide lower viewing zone and

25 a relatively wide intermediate zone; the dimensions of the intermediate and lower viewing zones being related to the prescribed addition power of the wearer.

16. A progressive ophthalmic lens element series according to Claim 15, wherein each lens element in the series has a progressive lens design exhibiting a small amount of addition power proximate the fitting cross, dependent on the prescribed addition power and the base curve.

30 17. A progressive ophthalmic lens series according to Claim 16, wherein

the addition power proximate the fitting cross of a progressive lens element is in the range from 0.05 to 0.40 D, the fitting cross addition power increasing with the addition power for each of the base curves, and with the increasing base curve for each addition power.

- 5 18. A progressive ophthalmic lens element series according to Claim 16, wherein the lens element series exhibits a slight decrease in the area of the zone clear for distance vision on the lens surface inside a 22 mm radius circle centred on the GC and constrained by the Add/4 diopters RMS power error contour ray traced in the as worn configuration for an infinite object distance with increasing
10 base curve.

19. A progressive ophthalmic lens element series according to Claim 18, wherein the lens elements exhibit an increase in corridor length within increasing addition power.

20. A progressive ophthalmic lens element series according to Claim 19,
15 wherein for low to medium addition powers the lens elements exhibit an increase in effective corridor length from approximately 10 to 12 mm; and for higher addition powers exhibit an effective corridor length of approximately 12 mm.

21. A progressive ophthalmic lens element series according to Claim 15,
20 wherein the progressive lens design of each lens element in the series includes a surface correction(s) in the peripheral regions of the lens element to reduce or minimise the phenomenon of swim.

22. A progressive ophthalmic lens element series according to Claim 21,
wherein the surface correction(s) function to reduce optical aberrations in lens surface areas including a pair of generally horizontally disposed opposed sectors
25 approximately $\pm 22.5^\circ$ above and below a generally horizontal axis passing through the fitting cross.

23. A progressive ophthalmic lens element series according to Claim 22, wherein the opposed sectors have a radius of approximately 15 mm or more.

24. A progressive ophthalmic lens element series according to Claim 23, wherein the surface correction takes the form of a reduction in the sagittal addition power variations within each of the opposed sectors.

25. A progressive ophthalmic lens element series according to Claim 24,
5 wherein the difference between maximum and minimum sagittal addition power within each of the opposed sectors is less than approximately $0.75 \times \text{Add}$ diopters.

26. A progressive ophthalmic lens element series according to Claim 15, wherein each element within the series exhibits a substantially constant area of clear vision on the lens surface within the lower viewing zone.

10 27. A progressive ophthalmic lens element series according to Claim 15, wherein each lens element includes a surface correction to improve optical properties proximate the peripheries of the lens element.

28. A progressive ophthalmic lens element series according to Claim 27,
15 wherein the distribution of RMS power error is varied proximate the peripheries of the upper and/or lower viewing zones to improve peripheral vision.

29. A progressive ophthalmic lens element series according to Claim 28, wherein the distribution of RMS power error exhibits a relatively low gradient proximate the distance periphery and a relatively high gradient proximate the near periphery.

20 30. A progressive ophthalmic lens element series according to Claim 29, wherein the base elements have the ratio of the maximum rate of change of the ray traced RMS power error along the 12 mm long vertical lines centred on the fitting cross (FC) and horizontally offset 15 mm from the FC to the maximum horizontal rate of change of the RMS power error at the level of the near vision
25 measurement point (NMP) varies from approximately 0.4 to approximately 0.6.

31. A method of designing an ophthalmic lens element including a first lens surface having

an upper viewing zone having a surface power corresponding to distance vision,

a lower viewing zone having a greater surface power than the upper viewing zone to achieve a refracting power corresponding to near vision; and

5 an intermediate zone extending across the lens element having a surface power varying from that of the upper viewing zone to that of the lower viewing zone and including

a corridor of relatively low surface astigmatism; the ophthalmic lens element including

10 a relatively high, relatively wide lower viewing zone; and

a relatively wide intermediate zone,

which method includes

selecting a merit function relating to at least one optical characteristic of the lens to be minimised with an appropriate distribution of the optimisation
15 weights on the lens surface; and

solving the global minimisation problem using the Finite Element Method;

and

fabricating an ophthalmic lens element having a lens surface shaped according to said optimised surface description.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
12 April 2001 (12.04.2001)

PCT

(10) International Publication Number
WO 01/25837 A1

(51) International Patent Classification⁷: **G02C 7/06**

(21) International Application Number: **PCT/AU00/01196**

(22) International Filing Date:
29 September 2000 (29.09.2000)

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
PQ 3220 1 October 1999 (01.10.1999) AU
PQ 3269 5 October 1999 (05.10.1999) AU

(71) Applicant (for all designated States except US): **SOLA INTERNATIONAL HOLDINGS LTD [AU/AU]**; Sheriffs Road, Lonsdale, South Australia 5160 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MORRIS, Michael, Alan [US/US]**; 2227 Old Ranch Place, Santa Rosa, CA

95405 (US). **FISHER, Scott, Warren [AU/AU]**; 12 Park Lane, Flagstaff Hill, South Australia 5159 (AU). **VAR-NAS, Saulius, Raymond [AU/AU]**; 22 McCoy Street, Brighton, South Australia 5048 (AU). **POPE, David, Robert [US/US]**; 1332 Gillpepper Lane, Rohnert Park, CA 94928 (US).


(74) Agent: **FREEHILLS CARTER SMITH BEADLE**; Level 46, 101 Collins Street, Melbourne, VIC 3000 (AU).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: **PROGRESSIVE LENS**



(57) Abstract: A progressive ophthalmic lens including a far vision zone, a near vision zone and an intermediate vision zone is provided having a relatively high, relatively wide near vision zone and a relatively wide intermediate zone. A surface correction(s) for reducing optical aberrations in peripheral regions of the lens may be provided within a pair of generally horizontally disposed opposed segments approximately $\pm 22.5^\circ$ above and below a generally horizontal axis passing through a fitting cross. Two or more progressive ophthalmic lenses differing in prescribed addition power may be placed in series to provide a range of distance prescriptions for one or more of emmetropes, hyperopes and myopes. A method of designing the progressive ophthalmic lens is also disclosed.

WO 01/25837 A1

Figure 1




Figure 2




Figure 3







Figure 4
Distance Objects



Near Objects





Figure 5




Figure 6




Figure 7




Figure 8
Distance Objects




Figure 9




Figure 10




Figure 11





Figure 12
Distance Objects



**COMBINED DECLARATION AND POWER OF ATTORNEY
FOR UTILITY OR DESIGN PATENT APPLICATION**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

Progressive Lens

the specification of which (check only one item below):

- ☐ is attached hereto.
- ☒ was filed as United States application
Number 10/089,781 on _____
and was amended on _____ (if applicable).
- ☐ was filed as PCT international application
Number _____ on _____
and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §§119 (a)-(d), 172 or 365 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

PRIOR FOREIGN/PCT APPLICATION(S) AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. §§119(a)-(d), 172 or 365:				
COUNTRY (if PCT, indicate "PCT")	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 U.S.C. §§119, 172 or 365	
AU	PQ 3220	1 October 1999 (01.10.1999)	Yes	No
AU	PQ 3269	5 October 1999 (05.10.1999)	Yes	No
PCT	PCT/AU00/01196	29 September 2000 (29.09.2000)	Yes	No
			Yes	No
			Yes	No

Combined Declaration and Power of Attorney
for Utility or Design Patent Application
Attorney's Docket No. 025265-232
Page 2 of 3

I hereby appoint the following attorneys and agent(s) to prosecute said application and to transact all business in the Patent and Trademark Office connected therewith and to file, prosecute and to transact all business in connection with international applications directed to said invention:

William L. Mathis	17,337	Eric H. Weisblatt	30,505	Bruce T. Wieder	33,815
Robert S. Swecker	19,885	James W. Peterson	26,057	Todd R. Walters	34,040
Platon N. Mandros	22,124	Teresa Stanek Rea	30,427	Ronni S. Jillions	31,979
Benton S. Duffett, Jr.	22,030	Robert E. Krebs	25,885	Harold R. Brown III	36,341
Norman H. Stepno	22,716	William C. Rowland	30,888	Allen R. Baum	36,086
Ronald L. Grudziecki	24,970	T. Gene Dillahunt	25,423	Brian P. O'Shaughnessy	32,747
Frederick G. Michaud, Jr.	26,003	Patrick C. Keane	32,858	Kenneth B. Leffler	36,075
Alan E. Kopecki	25,813	B. Jefferson Boggs, Jr.	32,344	Fred W. Hathaway	32,236
Regis E. Slutter	26,999	William H. Benz	25,952	Wendi L. Weinstein	34,456
Samuel C. Miller, III	27,360	Peter K. Skiff	31,917	Mary Ann Dillahunt	34,576
Robert G. Mukai	28,531	Richard J. McGrath	29,195	Donna M. Meuth	36,607
George A. Hovanec, Jr.	28,223	Matthew L. Schneider	32,814	Mark R. Kresloff	42,766
James A. LaBarre	28,632	Michael G. Savage	32,596		
E. Joseph Gess	28,510	Gerald F. Swiss	30,113		
R. Danny Huntington	27,903	Charles F. Wieland III	33,096		



21839

and:

Address all correspondence to:



21839

James W. Peterson
BURNS, DOANE, SWECKER & MATHIS, L.L.P.
P.O. Box 1404
Alexandria, Virginia 22313-1404


Address all telephone calls to: Samuel C. Miller at (703) 836-6620.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

FULL NAME OF SOLE OR FIRST INVENTOR	Michael Alan Morris
Signature	<i>Michael A. Morris</i>
Date	April 15, 2002
Residence (City, State, Country)	Santa Rosa, California, US CA
Citizenship	US
Mailing Address	2227 Old Ranch Place
City, State, ZIP, Country	Santa Rosa, California 95405
FULL NAME SECOND INVENTOR, IF ANY	Scott Warren Fisher
Signature	<i>Scott Warren Fisher</i>
Date	12/4/02
Residence (City, State, Country)	Flagstaff Hill, South Australia, AU SA
Citizenship	AU
Mailing Address	12 Park Lane
City, State, ZIP, Country	Flagstaff Hill, South Australia 5159

FULL NAME THIRD INVENTOR, IF ANY 3.0	Saulius Raymond Varnas
Signature	<i>[Signature]</i>
Date	12 Apr. 2002
Residence (City, State, Country)	Brighton, South Australia, AU SO. AU
Citizenship	AU
Mailing Address	22 McCoy Street
City, State, ZIP, Country	Brighton, South Australia 5048
FULL NAME FOURTH INVENTOR, IF ANY 4.0	David Robert Pope
Signature	<i>David R Pope</i>
Date	April 29, 2002
Residence (City, State, Country)	Rohnert Park, California, US CA
Citizenship	US
Mailing Address	1332 Gillpepper Lane
City, State, ZIP, Country	Rohnert Park, California 94928

United States Patent & Trademark Office
Office of Initial Patent Examination -- Scanning Division



Application deficiencies found during scanning:

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

☐ **Scanned copy is best available.**

Drawing figures are too dark.